



Sight Glasses

Visual indication of colour, flow and refrigerant quality in a refrigeration or A/C system



ENGINEERING YOUR SUCCESS.

SA Parker Sporlan SEE-ALL

Moisture Liquid Line Sight Glasses

Parker Sporlan SEE-ALL moisture and liquid indicator combines two functions of moisture and liquid indicator into a single economical product.

It takes the guess work out of servicing refrigeration and air conditioning equipment.

The indicator is a porous filter paper impregnated with a chemical salt that is sensitive to moisture.

The plated steel and copper fittings are copper to the heavily copper plated steel body. A glass disc is inserted in the body and heated just to the melting point under carefully controlled conditions.

The indicator is inserted from the back and held in place with a slotted cylinder.

See-All Sight Glasses with 1/4" through 1-1/8" ODF Solder connections are constructed with long fittings made from either heavily copper plated steel or copper.

However we recommend to protect the glass by calorie discharger **TB2 Thermal Block™** or to wrap it with a damp cloth. The indicator can be easily removed and replaced if necessary.

SEE-ALL moisture indicators with their large bezels and very sensible sensors help the users to check cleanness and dryness of systems and prevent failure of compressors.



Benefits

PS (MWP)	44.8 bar (650 psig)
TS	-40°C up to 66°C

● **Coating:** Polyester coating giving protection to 500 hours salt spray

● **Approvals:** UL file no. SA 3182
PED 97/23/EC - article 3.3

Features

Suitable for all CFC / HCFC / HFC refrigerant and their associated oils.

See-All Colour Indication	Moisture Content - ppm									
	R410A		R134a		R404A - R507		R407C		R22	
	24°C	52°C	24°C	52°C	24°C	52°C	24°C	52°C	24°C	52°C
Green- Dry	75	135	50	80	15	30	120	240	30	45
Yellow - Wet	150	250	200	225	90	140	280	560	90	130

For all requests, consult your nearest Parker Sporlan Wholesaler or contact us on:
racecustomerservice@parker.com / www.parker.com/race